



MULTICOM s.r.l.

MULTICOM SRL

Via E. Fermi, 170
46011 – Acquafredda sul Chiese (MN)
ITALY

Phone/Fax: 0376727248

info@multicom.srl.it | www.multicom.srl.it

COMBO MAT 600/300 H125

Identification

Example/ COMBO MAT 600/300 H125

600 : Nominal weight per square meter (g/m^2) of woven fabrics

300 : Nominal weight per square meter (g/m^2) of mat

Specification

Construction	Area Weight	Tolerance %	Remark
Woven Fabrics	600	±8.0	E glass woven roving EWR600
Mat	300	±8.0	E glass 2400 tex
Stitching	11	±8.0	Polyester 167d' tex
Total Area Weight	911	±8.0	
Stitch Gauge : 3.5Gauge/25mm			Stitch style : Tricot Stitch
Stitch length : 5.0mm			Loss on Ignition : 0.6%~4.0%
Moisture Content : ≤0.2%			Width : ±10mm
Colour tracer			--

Packing

Product is manufactured in form of a roll wound on a paper tube and then packed in a plastic film and placed within a cardboard carton. on pallet.

Above package is standard one, any other package style is negotiable by both of us.

Storage

It is recommended that the fiber glass are stored in a cool and dry environment. Recommended temperature range of storage is between 10 ~ 30°C and relative humidity between 50 ~ 75%. The fiber glass should remain in the packaging until just prior to use.

Remark: Other specification is available upon request